



SYNMAR FAUSTINA 75W-90 TDL | S300100 V25-2503

Description

The Synmar Faustina 75W-90 is a universal fully synthetic gear oil based on high quality synthetic base oils and special EP-additives to obtain the following properties:

- an excellent activity against high temperature load
- a very strong activity against wear, corrosion and foam
- very special extreme pressure properties
- widely usable

Application

The Synmar Faustina 75W-90 is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.

Performance Level

API GL-4, GL-5, MT-1
Mack GO-J
MAN M3343 Type S
MB 235.8
MIL-PRF-2105E
SAE J2360
Scania STO 1:0
Volvo 97312
ZF TE-ML 02B, 05A, 07A, 08, 16B, 17B, 21A

Typicals

Colour	Amber
Density at 15 °C, kg/l	0,869
Viscosity 40 °C, mm ² /s	83,90
Viscosity 100 °C, mm ² /s	15,40
Viscosity Index	195
Flash Point COC, °C	184
Pour Point, °C	-45

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.

SYNMAR B.V.

Albert Schweitzerstraat 7, 7131 PG Lichtenvoorde, The Netherlands
T: +31 (0) 33 303 3044 | M: info@synmar.nl