



Product specifications



Professional range

EXHAUST REPAIR PUTTY

Up to 1000°C

Wynn's Exhaust Repair Putty is a high quality adhesive/sealant based on sodium silicate and inorganic fillers. The product forms a permanent seal to repair exhaust systems.

Properties

- ✓ Ready to use paste.
- ✓ Heat resistant up to 1000°C.
- ✓ Bonds a wide range of materials.
- ✓ Non slip bonding.
- ✓ Asbestos free.
- ✓ Fast setting, especially when heat is applied.

Applications

- ✓ Sealing of automotive exhaust systems.
- ✓ General adhesive in all high temperature/fire retardant applications.
- ✓ Bonding of insulation materials.
- ✓ Sealing joints in furnaces.
- ✓ Sealing and repointing of open fire heating systems.

Technical data

Appearance	: ready to use Thixotropic Paste
Colour	: off white
Specific Gravity	: 1,84 – 1,88
Application temperature	: +5°C - +30°C
Temperature resistance	: + 1000°C

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium
 Tel: 32-3-766.60.20 - Fax: 32-3-778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.com

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.



Product specifications

Directions

- ✓ Ensure that the area to be repaired, is clean and free from loose rust.
- ✓ Dampen repair area with water and apply with a knife, forcing into whole crack to give strength.
- ✓ If necessary, soften putty with water.
- ✓ After use, replace lid firmly onto container.
- ✓ Once putty has been applied, start the engine and allow idling for a few minutes in order to accelerate the hardening process and to improve adhesion.
- ✓ When completely set, the exhaust system is ready for normal use.

Packaging

PN 10804 – 12x250 g – EN/NL/FR

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium
Tel: 32-3-766.60.20 - Fax: 32-3-778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.com

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.