



Product specifications



Professional range

ICE PROOF FOR DIESEL Concentrated Formula

Wynn's Ice Proof for Diesel has been developed:

- 1) to improve diesel fuel fluidity at low temperatures
- 2) to prevent settling of wax crystals.

Properties

- ✓ Can significantly improve cold weather performance across a broad spectrum of diesel fuel.
- ✓ Depresses the CFPP (Cold Filter Plugging Point) up to -30°C.
The CFPP reduction is dependent on the properties and the composition of the diesel fuel which has to be treated.
- ✓ Optimised to treat the widest possible range of middle distillate diesel fuel compositions for internal combustion engines.
- ✓ Slows down the formation of wax crystals.
- ✓ Prevents settling of wax crystals in the tank.
- ✓ Harmless to exhaust gas after-treatment systems.

Applications

- ✓ The best choice to reduce the effects of cold temperature on diesel fuels used in passenger cars, trucks, buses and boats, as well as heating oil and off-road fuels.
- ✓ Also for diesel fuel mixed with max. 30 % bio diesel.

Directions

- ✓ Add Ice Proof for Diesel prior to filling up.
- ✓ For optimum effect add Ice Proof for Diesel approx. 0°C above the cloud point of the diesel fuel.
- ✓ Dose: add 0,1 % by volume to diesel fuel (for instance add 1 litre to 1.000 litres of fuel).

Packaging

ITW Additives International – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium
Tel: 32-3-766.60.20 - Fax: 32-3.778-16.56 – E-mail: mail@wynns.eu – Website: www.wynns.com

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.



Product specifications

PN 22790 – 12x1 l – EN/FR/DE/NL/ES/IT/RU/HU/EL

PN 22796 – 4x5 l – EN/FR/DE/IT/RU

PN 22798 – 60 l – EN/FR/DE/NL/ES/IT/RU

PN 22799 – 200 l – EN/FR/DE/NL/ES/IT/RU

PN 22700 – 1000 l – EN/IT/RU

Note

Products treating low temperature characteristics of middle distillate diesel fuels will have only limited or no effect on summer grade diesel fuels.

ITW Additives International – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium
Tel: 32-3-766.60.20 - Fax: 32-3.778-16.56 – E-mail: mail@wynns.eu – Website: www.wynns.com

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.