







Professional range

## EXTREME COOLING SYSTEM DEGREASER

Wynn's Extreme Cooling System Degreaser removes oil and sludge in the cooling system of vehicles.

- Removes oil and sludge in the cooling system (caused by a leaking heat exchanger or cylinder head gasket).
- Degreases and cleans the entire cooling system.
- ✓ Keeps the residues in suspension whilst cleaning.
- Restores the heat transfer and the optimal operation of the controls within the cooling system.
- ✓ Excellent performance in all types of cooling liquid, including OAT coolant.
- ✓ Is completely soluble in water.
- ✓ Safe for rubber hoses, seals and all metals in the cooling system.

## **Applications**

✓ For all "water" cooled systems of petrol, diesel and LPG engines.

## **Directions**

- ✓ One bottle of 325ml treats cooling systems up to 7 litres.
- ✓ Add Wynn's Extreme Cooling System Degreaser directly into the radiator or via the expansion tank if part of the system circuit.
- ✓ Warm up the engine with the heater control in HOT position.
- ✓ Let the engine run at idle for 20 minutes.
- ✓ Stop the engine. Drain the system, flush with water, close the system and refill with water.
- ✓ Let the engine run at idle for 5 minutes. Heater still in HOT position.

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium Tel: 32-3-766.60.20 - Fax: 32-3.778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.com

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.

PN 25541\_44 - Last update: 02/02/2018





✓ Stop the engine. Drain the system, flush with water until clear, close the system and refill with coolant.

For engines with extremely heavy oil contamination a second treatment may be required.

For rust and scale removal, please use Wynn's Cooling System Flush.

Add Wynn's Cooling System Stop Leak as a leak preventive agent.

## Packaging

W25541 - 12x325 ml - EN/FR/IT/RU

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium Tel: 32-3-766.60.20 - Fax: 32-3.778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.com

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.

PN 25541\_44 - Last update: 02/02/2018